

**Tender text      GUIDE BARRIER****Guide barrier**

Overrideable. Recycled material. Lacquered yellow (other colours on demand)  
(BASSt test report must be submitted)

Width:                    242 mm  
Height:                   80 mm  
Length:                  1000 mm  
Weight:                  ca. 16 kg

**Accessories (optional):****Push-in reflector (same quantity as guide barrier)**

Overrideable. For insertion in guide barrier. Made of high impact and weather resistant plastic, with 7 glass beads (type Swareflex) on each side. Minimum ray value 12 mcd.  
(BASSt test report must be submitted)

**Delineator (in distances of 5 meter / 10 meter)**

Overrideable, self-rebounding. Height 530 mm. Made of flexible special synthetic, with reflective 3M-Folie RA 2 on one side or both sides. Including plastic wedges, which must be inserted in order to ensure full stability. Delineators are inserted and released from top.  
(BASSt test report must be submitted)

**Fixing material**

2 pegs S14, inkl. 2 screws 10x160 mm  
and 2 discs, galvanized

Maibach Verkehrssicherheits-  
und Lärmschutzeinrichtungen GmbH  
Bannholzstraße 4  
73037 Göppingen-Voralb  
Tel.: 07161/99760  
Fax.: 07161/997644  
www.maibach.com